



RUSTBUSTER CORROLAN PENETRATOR

PRODUCT DESCRIPTION

A ready to apply lanolin oil with reduced viscosity and surface tension for maintenance or use as a primer prior to application of Corrolan Pure. Or as a first stage injection primer prior to application of the Corrolan Active cavity treatment . Also, may be used as a general maintenance penetration fluid.

PRINCIPAL BENEFITS

- Acid and Salt resistant
- Resists wash off
- Hermetically seals
- Non-conductive to 70kw
- Non-toxic

APPLICATION INFORMATION

Product Description	Honey coloured lanolin-based wax , grease like consistency in cold temperatures.
Pack Description	400ml Aerosol, 1ltr Shutz Can, 5Ltr, 25Ltr, 60Ltr, 200Ltr
Application temperature	Can be applied to steel as low as - 5 c. The steel must be at least 3 degrees above the current dew point. (see Dew point calculator on website site)
Application	<p>Heating Corrolan Penetrator is not deemed necessary due to the low viscosity of the product.</p> <p>Brush, Rustbuster Pro-Wax Injection kit, Lemmer HD460 Pro-Rust proofing kit, Airless spray 26:1 at approx. 2000psi with s 517-519 tip size.</p> <p>A second coat of Corrolan Penetrator can be applied if the first is dry within 15-30minutes.</p> <p>Any excess should be wiped away with a lint free cloth before application of Corrolan Pure.</p>
Heating and Thinning	Thin using Corrolan Turbo safety solvent.
Cleaning	Clean up using Corrolan Turbo.
Safety	<p>Although Corrolan is a non-hazardous product PPE is recommended. Goggles, spray mask, spray suit and gloves.</p> <p>If you are allergic to Lanolin, do not use Corrolan products.</p>



Storage	Where possible store at 20c or higher. Colder or warmer storage will not damage the product but will decrease or increase the viscosity.
---------	--

For health and safety instructions please refer to the separate MSDS