SAFETY DATA SHEET

PARAMOSE AS10 ADHESIVE AND RESIN REMOVER INDUSTRIAL USE

Issued: 26/03/2007

Revision No: 2

Page 1

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: PARAMOSE AS10 ADHESIVE AND RESIN REMOVER INDUSTRIAL USE

Use of substance / preparation: Heavy duty Adhesive and resin remover

Company name: Chemicals Ltd

P.O.Box 88 Southport Merseyside PR8 5LH

United Kingdom
Tel: 01704 880800
Fax: 01704 880900

Emergency tel: 07966 660840 Email: sales@paintstripper.com

2. HAZARDS IDENTIFICATION

Main hazards: Limited evidence of a carcinogenic effect.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: DICHLOROMETHANE >60%

EINECS: 200-838-9 CAS: 75-09-2

[Xn] R40

• METHANOL 1-4.9%

EINECS: 200-659-6 CAS: 67-56-1

[F] R11; [T] R23/24/25; [T] R39/23/24/25

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat. There may be difficulty

swallowing. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: Absorption through the lungs can occur causing symptoms similar to those of ingestion.

4. FIRST AID MEASURES (ACTION)

Skin contact: Wash immediately with plenty of soap and water.Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to

drink immediately. Transfer to hospital as soon as possible.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

Issued: 26/03/2007 SAFETY DATA SHEET

PARAMOSE AS10 ADHESIVE AND RESIN REMOVER INDUSTRIAL USE

Page 2

5. FIRE-FIGHTING MEASURES

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool

containers.

Exposure hazards: In combustion emits toxic fumes.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin

and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details. Mark out the contaminated area with

signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to

prevent the escape of liquid.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by

an appropriate method.

7. HANDLING AND STORAGE

Handling requirements: Avoid the formation or spread of mists in the air. Avoid direct contact with the substance.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: DICHLOROMETHANE

WEL (8 hr TWA): 350 mg/m3 WEL (15 min STEL): 1060 mg/m3

METHANOL

WEL (8 hr TWA): 266 mg/m3 WEL (15 min STEL): 333 mg/m3

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure there is exhaust ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency. allways ensure

there is sufficient ventilation of the area

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid

Colourless

Odour: Sweet-smelling

Evaporation rate: Moderate

Solubility in water: Slightly soluble

Viscosity: Viscous

Issued: 26/03/2007

SAFETY DATA SHEET

PARAMOSE AS10 ADHESIVE AND RESIN REMOVER INDUSTRIAL USE

Page 3

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to avoid: Heat.

Materials to avoid: Strong oxidising agents. Strong acids.

Haz. decomp. products: In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Hazardous ingredients: DICHLOROMETHANE

ORL MUS LD50 4770 mg/kg ORL RAT LD50 5350 mg/kg SCU MUS LD50 6460 mg/kg

METHANOL

IVN RAT LD50 2131 mg/kg ORL MUS LD50 7300 mg/kg ORL RAT LD50 5628 mg/kg

Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

Mobility: Readily absorbed into soil.

Persistence and degradability: Biodegradable.

Bioaccumulative potential: No bioaccumulation potential.

Other adverse effects: Negligible ecotoxicity.

13. DISPOSAL CONSIDERATIONS

Disposal operations: Dispose via authorised waste disposal contractor to an approved waste disposal site.

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

NB: The user's attention is drawn to the possible existence of regional or national regulations

regarding disposal.

14. TRANSPORT INFORMATION

ADR / RID

UN no: 2810 **ADR Class:** 6.1

Packing group: III Classification code: T1

Shipping name: TOXIC LIQUID, ORGANIC, N.O.S. (DICHLOROMETHANE)

Labelling: 6.1 Hazard ID no: 60



Issued: 26/03/2007

SAFETY DATA SHEET

PARAMOSE AS10 ADHESIVE AND RESIN REMOVER INDUSTRIAL USE

Page 4

IMDG / IMO

UN no: 2810 Class: 6.1

Packing group: III EmS: F-A,S-A

Marine pollutant: .

Labelling: 6.1

IATA / ICAO

UN no: 2810 Class: 6.1

Packing group: III

Packing instructions: 611(P&CA); 618(CAO)

Labelling: 6.1

15. REGULATORY INFORMATION

Hazard symbols: Harmful.



Risk phrases: R40: Limited evidence of a carcinogenic effect.

Safety phrases: S2: Keep out of the reach of children.

S23: Do not breathe fumes.

S24/25: Avoid contact with skin and eyes.

S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.

S46: If swallowed, seek medical advice immediately and show this container or label.

S28: After contact with skin, wash immediately with plenty of water.

S51: Use only in well-ventilated areas.

S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label

where possible).

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical

advice.

Haz. ingredients (label): DICHLOROMETHANE

Note: The regulatory information given above only indicates the principal regulations specifically

applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all

applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Risk phrases used in s.3: R40: Limited evidence of a carcinogenic effect.

R11: Highly flammable.

R23/24/25: Toxic by inhalation, in contact with skin and if swallowed.

SAFETY DATA SHEET

PARAMOSE AS10 ADHESIVE AND RESIN REMOVER INDUSTRIAL USE

Page 5

R39/23/24/25: Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.