

Page 1/7

Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 15.08.2007

Revision: 15.08.2007

 Trade name: <u>DINITROL 4941</u> Application of the substance / the preparation Anticorrosion additive Manufacturer/Supplier: EFTEC Ltd. Rhigos, Aberdare, Mid-Glamorgan CF44 9UE, United Kingdom EFTEC Aftermark et GmbH Pyrmonterstr. 76 D-32676 Lügde Further information obtainable from: +44(0)16 85 81 54 00 Q&E Plastisols Information in case of emergency: +44(0)16 85 81 54 00 Q&E Plastisols Information in case of emergency: +44(0)16 85 81 54 00 Plazards identification Plazard description: Not applicable. Information concerning particular hazards for human and environment: The product has to be labelled due to the calculation procedure of the "General Classifi guideline for preparations of the EU" in the latest valid version. At long or repeated contact with skin it may cause dermatitis due to the degreasing effect solvent. Has a narcotizing effect. R 10 Flammable. R 66 Repeated exposure may cause skin dryness or cracking. R 67 Vapours may cause drowsiness and dizziness. Classification is according to the latest editions of the EU-lists, and extended by compa literature data. Additional information: The viscosity of the product is >7CSt at 40°C (or more than 30 sec with ISO 3). Classification R65 (aspiration risk) is not required. The peroleum naphtha / petroleum distillate / lubricating oil meet the requirements for no classified as carcinogenic (<0,1% benzene alt<3% (w/w) DMSO extract (IP 346)). 	· Product details		
Hazard description: Not applicable.Information concerning particular hazards for human and environment:The product has to be labelled due to the calculation procedure of the "General Classifiguideline for preparations of the EU" in the latest valid version.At long or repeated contact with skin it may cause dermatitis due to the degreasing effectsolvent.Has a narcotizing effect.R 10 Flammable.R 66 Repeated exposure may cause skin dryness or cracking.R 67 Vapours may cause drowsiness and dizziness.Classification is according to the latest editions of the EU-lists, and extended by compaliterature data.Additional information:The viscosity of the product is >7cSt at 40°C (or more than 30 sec with ISO 3). ClassificatioR65 (aspiration risk) is not required.The petroleum naphtha / petroleum distillate / lubricating oil meet the requirements for no	• Application of the su • Manufacturer/Supple EFTEC Ltd. Rhigos, EFTEC Aftermarket • Further information	ubstance / the preparation Anticorrosion additive l ier: Aberdare, Mid-Glamorgan CF44 9UE, United Kingdom GmbH Pyrmonterstr. 76 D-32676 Lügde e obtainable from: +44(0)16 85 81 54 00 Q&E Plastisols	
 Information concerning particular hazards for human and environment: The product has to be labelled due to the calculation procedure of the "General Classific guideline for preparations of the EU" in the latest valid version. At long or repeated contact with skin it may cause dermatitis due to the degreasing effect solvent. Has a narcotizing effect. R 10 Flammable. R 66 Repeated exposure may cause skin dryness or cracking. Classification system: The classification is according to the latest editions of the EU-lists, and extended by compaliterature data. Additional information: The viscosity of the product is >7cSt at 40°C (or more than 30 sec with ISO 3). Classification R65 (aspiration risk) is not required. The petroleum naphtha / petroleum distillate / lubricating oil meet the requirements for no 	2 Hazards identifie	cation	
 Information concerning particular hazards for human and environment: The product has to be labelled due to the calculation procedure of the "General Classific guideline for preparations of the EU" in the latest valid version. At long or repeated contact with skin it may cause dermatitis due to the degreasing effect solvent. Has a narcotizing effect. R 10 Flammable. R 66 Repeated exposure may cause skin dryness or cracking. Classification system: The classification is according to the latest editions of the EU-lists, and extended by compaliterature data. Additional information: The viscosity of the product is >7cSt at 40°C (or more than 30 sec with ISO 3). Classification R65 (aspiration risk) is not required. The petroleum naphtha / petroleum distillate / lubricating oil meet the requirements for no 	· Hazard description:	Not applicable	
	The product has to guideline for prepar At long or repeated solvent. Has a narcotizing eff R 10 Flammable. R 66 Repeated expos R 67 Vapours may co Classification system The classification is literature data. • Additional informat The viscosity of the R 65 (aspiration risk The petroleum naph	be labelled due to the calculation procedure of the "General ations of the EU" in the latest valid version. I contact with skin it may cause dermatitis due to the degreas Fect. Sure may cause skin dryness or cracking. Tuse drowsiness and dizziness. according to the latest editions of the EU-lists, and extended to ion: product is >7cSt at 40°C (or more than 30 sec with ISO 3). Cla) is not required. tha / petroleum distillate / lubricating oil meet the requirement	sing effect by company assificatio
	B Composition/inf	prmation on ingredients	
Composition/information on ingredients	• Description: Hydroc	arbon solvent based corrosion rust preventive.	
• Chemical characterization • Description: Hydrocarbon solvent based corrosion rust preventive.	<u>е</u>		
• Chemical characterization • Description: Hydrocarbon solvent based corrosion rust preventive. • Dangerous components:			23
Chemical characterization Description: Hydrocarbon solvent based corrosion rust preventive. Dangerous components: CAS: 64742-48-9 Naphtha (petroleum), hydrotreated heavy 2.	CAS: 64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic	
 Chemical characterization Description: Hydrocarbon solvent based corrosion rust preventive. Dangerous components: CAS: 64742-48-9 Naphtha (petroleum), hydrotreated heavy EINECS: 265-150-3 Xn; R 10-65-66-67 	EINECS: 265-169-7		

· After inhalation: Supply fresh air.

(Contd. on page 2) GB

Printing date 15.08.2007

Revision: 15.08.2007

Trade name: DINITROL 4941

(Contd. of page 1)

- After skin contact: Remove contaminated clothing. Wash skin with soap and water.
- After eye contact: Rinse opened eye for several minutes under running water.

• After swallowing: Seek medical treatment.

5 Fire-fighting measures

• Suitable extinguishing agents:

Foam

Carbon dioxide Fire-extinguishing powder Water haze

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Protective equipment: No special measures required.
- Additional information Cool endangered receptacles with water spray.

6 Accidental release measures

· Person-related safety precautions:

Ensure adequate ventilation

Avoid contact with skin, eyes and clothes.

Keep away from ignition sources.

Wear protective equipment. Keep unprotected persons away.

- Measures for environmental protection: Do not allow to enter sewers/ surface or ground water.
- Measures for cleaning/collecting:

Dispose of the material collected according to regulations. Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

7 Handling and storage

· Handling:

· Information for safe handling:

- No special measures required.
- Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- · Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· Storage:

- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
- Keep container tightly sealed.

Protect from heat and direct sunlight.

8 Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 3)

Printing date 15.08.2007

Revision: 15.08.2007

Trade name: DINITROL 4941

(Contd. of page 2)

• Ingredients with limit values that require monitoring at the workplace: 64742-48-9 Naphtha (petroleum), hydrotreated heavy

TWA Long-term value: 1000 mg/m^3

64742-65-0 Distillates (petroleum), solvent-dewaxed heavy paraffinic

OEL Short-term value: 10 mg/m³ Long-term value: 5 mg/m³ Mineral Oil mist

· Additional information: The lists valid during the making were used as basis.

- · Personal protective equipment:
- General protective and hygienic measures: Wash hands before breaks and at the end of work.
- Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

· Material of gloves

Neoprene gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

• General Information			
Form:	Structurally viscous		
Colour:	Black		
Odour:	Characteristic		
• Change in condition Melting point/Melting re			
Boiling point/Boiling ra	nge: 175°C		
Boiling point/Boiling ra · Flash point:	nge: 175°C 43°C (ISO 2719)		
0.	<u> </u>		

Printing date 15.08.2007

Revision: 15.08.2007

Trade name: DINITROL 4941

	(Contd. of page 3	
• Danger of explosion:	Product is not explosive. However, formation of explosive vapour mixtures are possible.	
· Explosion limits:		
Lower:	0.6 Vol %	
Upper:	7.0 Vol %	
· Vapour pressure at 20°C:	1.0 hPa	
• Density at 20°C:	1.04000 g/cm ³	
· Solubility in / Miscibility with water:	h Not miscible or difficult to mix.	
· Viscosity:		
Dynamic at 20°C:	850 mPas	
· Solvent content:		
Organic solvents:	36.7 %	
· Solids content:	63.0 %	

10 Stability and reactivity

• Thermal decomposition / conditions to be avoided:

- No decomposition if used according to specifications.
- · Dangerous reactions No dangerous reactions known.
- Dangerous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Acute toxicity:

· LD/LC50 values relevant for classification:

64742-48-	9 Naphtha	(petroleum), hydrotreated heavy
Oral	LD50	>5000 mg/kg (rat)

Inhalative	LC50/4h	10 mg/l (RAT)
Dermal	LD50	>3000 mg/kg (rab)

• Primary irritant effect:

 \cdot on the skin: The product degreases the skin.

• on the eye: Irritation to eyes possible after a long exposure time.

· Sensitization: No sensitizing effects known.

· Inhalation:

May cause headache, dizziness, tiredness and indisposition. At high concentrations reaction time and memory may deteriorate and unconsciousness may occur. Long or often repeated inhalation of high concentrations may cause permanent damage to the nervous system.

· Ingestion: May cause similar symptoms as for inhalation.

<u>12 Ecological information</u>

· General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

(Contd. on page 5)

GB

Printing date 15.08.2007

Revision: 15.08.2007

Trade name: DINITROL 4941

(Contd. of page 4)

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13 Disposal considerations

· Product:

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 00 00 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS

08 01 00 wastes from MFSU and removal of paint and varnish

08 01 11 waste paint and varnish containing organic solvents or other dangerous substances

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

14 Transport information

· Land transport ADR/RID (cross-border)



· ADR/RID class: 3 (F1) Flammable liquids.

- · Danger code (Kemler): 30
- · UN-Number: 1139
- · Packaging group: Ш 3
- · Hazard label
- · Description of goods: 1139 COATING SOLUTION (not viscous)
- · Maritime transport IMDG:



3 · UN Number: 1139 · Label 3 · Packaging group: Ш

- · EMS Number: F-E, S-E
- Marine pollutant: No

· Proper shipping name: COATING SOLUTION

· Air transport ICAO-TI and IATA-DGR:



· ICAO/IATA Class: 3

(Contd. on page 6)

Printing date 15.08.2007

Revision: 15.08.2007

Trade name: DINITROL 4941

(Contd. of page 5)

• **UN/ID Number:** 1139

·Label

• Packaging group: III • Proper shipping name: COATING SOLUTION

3

· Transport/Additional information:

ADR: VOL> 450 l, KL 3 F1, PG III IMDG: VOL> 30 l, KL 3, PG III

15 Regulatory information

· Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· Risk phrases:

10 Flammable.

- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.

· Safety phrases:

- 2 Keep out of the reach of children.
- 23 Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).
- 36 Wear suitable protective clothing.
- 43 In case of fire, use sand, carbon dioxide or powdered extinguishing agent. Never use water.
- 46 If swallowed, seek medical advice immediately and show this container or label.
- 56 Dispose of this material and its container to hazardous or special waste collection point.

·National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· Technical instructions (air):

Class Share in % NK 25-50

• Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

• EU-VOC: 36.67 %

16 Other information

The information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our product from the point of view of safety requirements and is not intended to guarantee any particular property.

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant R-phrases

10 Flammable.

65 Harmful: may cause lung damage if swallowed.66 Repeated exposure may cause skin dryness or cracking.67 Vapours may cause drowsiness and dizziness.

· Department issuing MSDS: Q&E Department

(Contd. on page 7)

⁻ GB

Printing date 15.08.2007

Revision: 15.08.2007

(Contd. of page 6)

GB

Trade name: DINITROL 4941

· Contact:

J. Maxwell

john.maxwell@eftecltd.co.uk

 $\cdot *$ Data compared to the previous version altered.