

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 16.08.2007

Revision: 16.08.2007

1 Identification of the substance/preparation and of the company/undertaking

· **Product details**

· **Trade name:** DINITROL 3125

· **Application of the substance / the preparation** Surface protection

· **Manufacturer/Supplier:**

EFTEC Ltd. Rhigos, Aberdare, Mid-Glamorgan CF44 9UE, United Kingdom

EFTEC Aftermarket GmbH Pyrmonterstr. 76 D-32676 Lügde

· **Further information obtainable from:** +44(0)16 85 81 54 00 Q&E Plastisols

· **Information in case of emergency:** +44(0)16 85 81 54 00

2 Hazards identification

· **Hazard description:** Not applicable.

· **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

Has a narcotizing effect.

R 10 Flammable.

R 66 Repeated exposure may cause skin dryness or cracking.

R 67 Vapours may cause drowsiness and dizziness.

· **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

· **Additional information:**

The petroleum naphtha / petroleum distillate / lubricating oil meet the requirements for not being classified as carcinogenic (<0,1% benzene alt<3% (w/w) DMSO extract (IP 346)).

The viscosity of the product is >7cSt at 40°C (or more than 30 sec with ISO 3). Classification with R65 (aspiration risk) is not required.

3 Composition/information on ingredients

· **Chemical characterization**

· **Description:** Hydrocarbon solvent based corrosion rust preventive.

· **Dangerous components:**

CAS: 64742-48-9 EINECS: 265-150-3	Naphtha (petroleum), hydrotreated heavy ☒ Xn; R 10-65-66-67	50-100%
CAS: 64742-65-0 EINECS: 265-169-7	Distillates (petroleum), solvent-dewaxed heavy paraffinic	10-25%
CAS: 25307-17-9 EINECS: 246-807-3	Bis(2-hydroxyethyl) oleylamine ☒ C, ☒ Xn, ☒ N; R 22-34-50	0.1-1%

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

GB

(Contd. on page 2)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 16.08.2007

Revision: 16.08.2007

Trade name: DINITROL 3125

(Contd. of page 1)

* 4 First-aid measures

- **After inhalation:** Supply fresh air.
- **After skin contact:** Remove contaminated clothing. Wash skin with soap and water.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** Seek medical treatment.

* 5 Fire-fighting measures

- **Suitable extinguishing agents:**
 - Water haze
 - Foam
 - Fire-extinguishing powder
 - Carbon dioxide
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Protective equipment:** No special measures required.
- **Additional information** Cool endangered receptacles with water spray.

* 6 Accidental release measures

- **Person-related safety precautions:**
 - Ensure adequate ventilation
 - Keep away from ignition sources.
 - Avoid contact with skin, eyes and clothes.
 - Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:** Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:**
 - Dispose of the material collected according to regulations.
 - Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 - Ensure adequate ventilation.
 - Do not flush with water or aqueous cleansing agents

* 7 Handling and storage

- **Handling:**
- **Information for safe handling:**
 - No special measures required.
 - Ensure good ventilation/exhaustion at the workplace.
 - Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
 - Use explosion-proof apparatus / fittings and spark-proof tools.
 - Keep ignition sources away - Do not smoke.
 - Protect against electrostatic charges.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
 - Store receptacle in a well ventilated area.
 - Keep container tightly sealed.
 - Protect from heat and direct sunlight.

GB

(Contd. on page 3)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 16.08.2007

Revision: 16.08.2007

Trade name: DINITROL 3125

(Contd. of page 2)

8 Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.

· **Ingredients with limit values that require monitoring at the workplace:**

64742-48-9 Naphtha (petroleum), hydrotreated heavy

TWA Long-term value: 1000 mg/m³

64742-65-0 Distillates (petroleum), solvent-dewaxed heavy paraffinic

OEL Short-term value: 10 mg/m³

Long-term value: 5 mg/m³

Mineral Oil mist

· **Additional information:** The lists valid during the making were used as basis.

· **Personal protective equipment:**

· **General protective and hygienic measures:** Wash hands before breaks and at the end of work.

· **Respiratory protection:**

Suitable respiratory protective device recommended.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**



Protective gloves

· **Material of gloves**

Neoprene gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

· **Body protection:** Protective work clothing

9 Physical and chemical properties

· **General Information**

Form:	Fluid
Colour:	Dark brown
Odour:	Characteristic

· **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 170°C

· **Flash point:** 30°C (ISO 2719)

(Contd. on page 4)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 16.08.2007

Revision: 16.08.2007

Trade name: DINITROL 3125

(Contd. of page 3)

· Ignition temperature:	240°C
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	0.6 Vol %
Upper:	7.0 Vol %
· Vapour pressure at 20°C:	1 hPa
· Density at 20°C:	0.83 g/cm ³
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Viscosity:	
Kinematic:	32 s DIN 3
· Solvent content:	
Organic solvents:	54.0 %
· Solids content:	43.0 %

* 10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Dangerous reactions** No dangerous reactions known.
- **Dangerous decomposition products:** No dangerous decomposition products known.

* 11 Toxicological information

- **Acute toxicity:**

- **LD/LC50 values relevant for classification:**

64742-48-9 Naphtha (petroleum), hydrotreated heavy

Oral	LD50	>5000 mg/kg (rat)
------	------	-------------------

Dermal	LD50	>3000 mg/kg (rab)
--------	------	-------------------

Inhalative	LC50/4h	10 mg/l (RAT)
------------	---------	---------------

- **Primary irritant effect:**

- **on the skin:**

Degreases the skin which with long or often repeated contact may cause reddening and sometimes eczema. In combination with bad personal hygiene, it may cause dermatitis, oil acne or other skin changes.

- **on the eye:** Irritation to eyes possible after a long exposure time.

- **Sensitization:** No sensitizing effects known.

- **Inhalation:**

May cause headache, dizziness, tiredness and indisposition. At high concentrations reaction time and memory may deteriorate and unconsciousness may occur. Long or often repeated inhalation of high concentrations may cause permanent damage to the nervous system.

- **Ingestion:**

May cause similar symptoms as for inhalation.

(Contd. on page 5)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 16.08.2007

Revision: 16.08.2007

Trade name: DINITROL 3125

(Contd. of page 4)

Risk of chemical pneumonia if the product reaches the lungs at vomiting or similar.

12 Ecological information

- **Ecotoxicological effects:**
- **Remark:** The solvent can be bioaccumulated.
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13 Disposal considerations

- **Product:**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 11	waste paint and varnish containing organic solvents or other dangerous substances

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· Land transport ADR/RID (cross-border)



- **ADR/RID class:** 3 (F1) Flammable liquids.
- **Danger code (Kemler):** 30
- **UN-Number:** 1139
- **Packaging group:** III
- **Hazard label:** 3
- **Description of goods:** 1139 COATING SOLUTION (not viscous)

· Maritime transport IMDG:



- **IMDG Class:** 3
- **UN Number:** 1139
- **Label:** 3
- **Packaging group:** III

(Contd. on page 6)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 16.08.2007

Revision: 16.08.2007

Trade name: DINITROL 3125

(Contd. of page 5)

- **EMS Number:** F-E,S-E
- **Marine pollutant:** No
- **Proper shipping name:** COATING SOLUTION

- **Air transport ICAO-TI and IATA-DGR:**



- **ICAO/IATA Class:** 3
- **UN/ID Number:** 1139
- **Label:** 3
- **Packaging group:** III
- **Proper shipping name:** COATING SOLUTION

* 15 Regulatory information

- **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

- **Risk phrases:**

*10 Flammable.
66 Repeated exposure may cause skin dryness or cracking.
67 Vapours may cause drowsiness and dizziness.*

- **Safety phrases:**

*23 Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).
36 Wear suitable protective clothing.
43 In case of fire, use sand, carbon dioxide or powdered extinguishing agent. Never use water.
45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
60 This material and its container must be disposed of as hazardous waste.*

- **National regulations:**

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

- **Technical instructions (air):**

Class	Share in %
NK	50-100

- **Waterhazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.
- **EU-VOC:** 54.36 %

* 16 Other information

The information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our product from the point of view of safety requirements and is not intended to guarantee any particular property.

- **Relevant R-phrases**

10 Flammable.

(Contd. on page 7)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 16.08.2007

Revision: 16.08.2007

Trade name: DINITROL 3125

(Contd. of page 6)

22 Harmful if swallowed.

34 Causes burns.

50 Very toxic to aquatic organisms.

65 Harmful: may cause lung damage if swallowed.

66 Repeated exposure may cause skin dryness or cracking.

67 Vapours may cause drowsiness and dizziness.

· **Department issuing MSDS:** Q&E Department

· **Contact:**

J. Maxwell

john.maxwell@eftecltd.co.uk

· *** Data compared to the previous version altered.**

GB