

RUSTBUSTER CHLOR-X

PRODUCT DESCRIPTION

CHLOR-X is an organic bonding chemical blend which aids in the removal of chlorides, sulphates and surface reacted salts. Contains no volatile organic compounds (VOC's), and is biodegradable.

CHLOR-X is recommended for use in a maintenance wash solution to reduce corrosion and as part of surface preparation prior to application of primers or coatings on a variety of surfaces, including ferrous and non-ferrous metals, concrete, wood, plastics and others.

APPLICATION INFORMATION	
Surface Preparation	Best surface preparation yields the best results. If hydrocarbons are present, they should be removed prior to salt removal. Barrier materials, such as rust or scale or delaminated coatings, should be removed prior to salt removal. Sufficient mechanical force, such as high-pressure water or wet abrasive blast, may be utilized so barrier materials are removed as part of salt removal procedures.
	CHLOR-X can be used as after application of Rustbuster PHOS-KLEEN products to lift any surface salts where the Phos-Kleen has been allowed to pool and dry leaving a residue.
Application	CHLOR-X can be introduced and applied by a variety of means. See Directions for hand cleaning, pressure washing, UHP water jetting and wet abrasive blasting methods. Contact RUSTBUSTER LTD or an Authorized Distributor for other methods or technical support. Before and after cleaning a small sample area (usually 25 Sq. Ft.), test the surface for contamination. Adjust travel speed, pressure or dilution as necessary and retest to assure desired cleanliness level is achieved. It is not necessary to use the entire contents. Partially filled containers should be closed tightly.
Typical coverage	10-30 Sq. metres per Ltr (approx.)
Cleaning	Flush with clean fresh water
Safety	Wear suitable protective clothing, gloves, face mask and eye protection



For health and safety instructions please refer to the separate MSDS