



RUSTBUSTER WELD THRU LOW BURN PRIMER

PRODUCT DESCRIPTION

Rustbuster Weld Thru low burn primer is a two pack, modified zinc silicate shopprimer.

PRINCIPAL BENEFITS

- Preconstruction primer for blast cleaned steel surfaces.
- Low burn.
- Reduced health risk during welding and cutting.
- Reduction of weld defects

APPLICATION INFORMATION

Product Description	Low burn modified zinc silicate primer
Colour	Red
Solids	62+2%
Theoretical Coverage	20 Square metres per litre
Application thickness range	25-40microns WFT 15-25microns DFT
Dry to Touch	1 minute
Surface preparation	D.A or power tool cleaned steel to St2 (ISO 8601-1:1988/SS 05 5900) Blast cleaned steel to SA 2.5 (ISO 8501-1:1988/SS 05 5900)
Directions of Use	The two components liquid and resin are supplied in separate containers and must be mixed as follows, Pour out the liquid into a mixing cup and add the resin to this at a ratio of 6.9 liquid to 2.4 resin mixing continuously. Continuous agitation is necessary.
Cleaning	Water
Safety	Wear suitable protective clothing, gloves, face mask and eye protection

For health and safety instructions please refer to the separate MSDS