



RUSTBUSTER CORROLAN ACTIVE

PRODUCT DESCRIPTION

A self-healing rust proofing Corrolan oil for use in cavities and enclosed areas, box sections, sills, chassis rails, doors and any other cavities in steel or aluminium. A low odour product using low voc odourless safety solvents.

PRINCIPAL BENEFITS

- Acid and Salt resistant
- Resists wash off
- Hermetically seals
- Non-conductive to 70kw
- Non-toxic

APPLICATION INFORMATION

Product Description	Honey coloured lanolin-based wax , grease like consistency in cold temperatures.
Pack Description	400ml Aerosol, 1ltr Shutz Can, 5Ltr, 25Ltr, 60Ltr, 200Ltr
Application temperature	Can be applied to steel as low as - 5 c. The steel must be at least 3 degrees above the current dew point. (see Dew point calculator on website site)
Application	Heating Corrolan Penetrator is not deemed necessary due to the low viscosity of the product. Rustbuster Pro-Wax Injection kit, Lemmer HD460 Pro-Rust proofing kit
Heating and Thinning	It is not recommended to thin Corrolan Active
Cleaning	Clean up using Corrolan Turbo.
Safety	Although Corrolan is a non-hazardous product PPE is recommended. Goggles, spray mask, spray suit and gloves. If you are allergic to Lanolin, do not use Corrolan products.
Storage	Where possible store at 20c or higher. Colder or warmer storage will not damage the product but will decrease or increase the viscosity.



For health and safety instructions please refer to the separate MSDS