



RUSTBUSTER CORROLAN ACTIVE

PRODUCT DESCRIPTION

A self-healing rust proofing Corrolan oil for use in cavities and enclosed areas, box sections, sills, chassis rails, doors and any other cavities in steel or aluminium. A low odour product using low voc odourless safety solvents.

PRINCIPAL BENEFITS

- Acid and Salt resistant
- Resists wash off
- Hermetically seals
- Non-conductive to 70kw
- Non-toxic

APPLICATION INFORMATION

Product Description	Honey coloured lanolin-based wax , grease like consistency in cold temperatures.
Pack Description	400ml Aerosol, 1ltr Shutz Can, 5Ltr, 25Ltr, 60Ltr, 200Ltr
Application temperature	Can be applied to steel as low as - 5 c. The steel must be at least 3 degrees above the current dew point. (see Dew point calculator on website site)
Application	Rustbuster Pro-Wax Injection kit, Lemmer HD460 Pro-Rust proofing kit, Elite Rustproofing Injection Kit.
Heating and Thinning	It is not recommended to thin Corrolan Active Heating: Warm Corrolan Active to 20-40°C to reduce viscosity and facilitate spraying. During colder months, heating to 30-40°C may be necessary.
Cleaning	Clean up using Corrolan Turbo.
Safety	Although Corrolan is a non-hazardous product PPE is recommended. Goggles, spray mask, spray suit and gloves. If you are allergic to Lanolin, do not use Corrolan products.
Storage	Store at 20°C or higher for optimal consistency. Colder or warmer storage will not damage the product but will affect viscosity. Keep containers sealed when not in use to prevent contamination.



Compatibility	Can be used over most existing coatings, but a compatibility test is recommended before full application.

The information contained in the Technical Data Sheets below is correct to the best of [Rustbuster](http://Rustbuster.co.uk) Ltd.'s knowledge. However, you must ensure that the goods are suitable for your needs through independent testing or other processes.

Rustbuster Ltd makes no warranty, representation, or guarantee regarding the information in this Technical Data Sheet or the suitability of its products and services for any particular purpose. Rustbuster Ltd assumes no liability arising from the application or use of the goods, except for any liability that cannot be limited by law, including but not limited to:

- (a) death or personal injury caused by negligence;
- (b) fraud or fraudulent misrepresentation; and

- (c) breach of the terms implied by section 12 of the Sale of Goods Act 1979.

In such circumstances, Rustbuster Ltd's total liability shall not exceed the cost of the goods. This total liability includes liability in contract, tort, negligence, breach of statutory duty, or otherwise. It is the customer's responsibility to ensure that the guidance in the Technical Data Sheet is followed.

For health and safety instructions please refer to the separate MSDS